



WIRE ARRANGEMENT				
P1	COLOR	P2	P3	
1	RED	9		CABLE 1
2	WHITE	7		
3	GREEN	5		
4	BLACK	3		
5	RED		10	CABLE 2
6	WHITE		8	
7	GREEN		6	
8	BLACK		4	
CASE	CABLE 1 BRAID SHIELD		2	
	CABLE 2 BRAID SHILED			

8	NUTS(4*40)4.75x2.0mm.
7	HS TUBE
6	HOUSIGN: PV-H-2X05
5	TERMINAL: PV-T-22
4	PLASTIC HOOD MOLDED BLACK.
3	INNER MOLD: LD-PE FOUND FOUNDRY.
2	USB CONN: A TYPE,FEMALE,DOUBLE,SOLDER TYPE,INSULATOR:WHITE.
1	CABLE: UL2725 28AWGx1P+24AWGx2C+AEB OD=4.5±0.15mm PVC JACKET BLACK
NO.	NOTE

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT / mm

SCALE 1:1

.XX±

DATE

.XXX±

ANG±

SIZE A4

P PROJECTION



ORDER INFORMATION

PVUBX12-B054APE2428-F20N

SERIES

508mm

FEMALE

24,28 AWG

PANEL

2X05 TO 4AX2

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: **USBA F Dual TO 2.54 DP 10P L:508mm BLACK**