



SHELL	BRAID	5
4	BLACK	4
3	GREEN	3
2	WHITE	2
1	RED	1
Conn.2		Conn.4
SHELL	BRAID	5
4	BLACK	4
3	GREEN	3
2	WHITE	2
1	RED	1
Conn.1	COLOR	Conn.3

Pin Assignment

- 6. SCREW:4-40# 4 PCS
- 5. HEAT SHRINK TUBING:∅8.0*20mm&∅1.5*42mm 3 PCS
- 4. PVC MOLDING 35P 00ΔDR:UL2725 9
- 3. Connt.3:杜邦 2.54mm-5PIN*1 00ΔDR:BLACK 1 pcs
杜邦2.54mm Terminal 8 pcs
- 2. Connt.1&2: USB"A"TYPE FEMALE REV 1.1 2 pcs
- 1. CABLE: UL2725 28#/1P+24#/2C+AEB REV2.0 2 PCS
JACKET 00ΔDR: BEIGE ∅D:3.5±0.1mm

ELECTRICAL PROPERTIES:

- 1. 100% OPEN SHORT MIS-WIRE TEST
- 2. Contact Resistance: 2 ohm max
- 3. Insulation Resistance: 5Mega ohm MIN
- 4. Hipot test:DC 300V 10ms

	PART NO. PVUBX22-054AMB-F25C		RoHS Compliant	
	DWG NO. PVUBX22-054AMB-F25C	CHECKED BY CY	TOLERANCES ARE	
	FILE NO.		DRAWING BY	DESCRIPTION: USB SLOT A TYPE FEMALE*2 TO HOUSING 1*5 L: 25CM
	UNIT / mm	SCALE 1:1	PROJECTION	
			.X ± 0.2	REVISIONS
			.XX ±	HK
			.XXX ±	DATE
			AWG	