



2=gr Litzen anlöten  
 3=ge und mit Schrumpfschlauch  
 4=gn 1/10" LgNr.: 287429  
 6=ws isolieren  
 7=bl  
 Pin5 entfernen

LiFY 0,25qmm gelb LgNr.:285324  
 LiFY 0,25qmm weiß LgNr.:285326  
 LiFY 0,25qmm grün LgNr.:285327  
 LiFY 0,25qmm blau LgNr.:285328  
 LiFY 0,25qmm grau LgNr.:285329

Buchsengehäuse 2x4pol.  
 LgNr.: 252937  
 Crimpkontakt LgNr.: 252934  
 Kodierstift (auf Pin 5 )  
 LgNr.: 252958

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PJECTION

X, ±  
 .X ±  
 .XX ±  
 .XXX ±  
 ANG ±

照片框

ORDER INFORMATION

PVX2-B04B0424-E40C-LF

SERIES

LEADFREE  
 400mm  
 MALE TO FEMALE  
 24 AWG  
 08 TO 08 WAY

DESCRIPTION: