


### Technical Data :

Insulator Material: High Temperature Thermoplastic,LCP,UL 94V-0  
 Contact : Copper alloy  
 Plating: Matte Tin plated over Nickel  
 Current Rating : 6 Amp  
 Insulator resistance : 1000 Megohms min.  
 Dielectric withstanding : AC 500V for 1 Minute.  
 DC 707V for 1 Minute.  
 Operating Temperature: -55°C to +105°C.  
 Max. processing Temp: 230°C for 30-60 seconds.  
 260°C for 10 seconds.  
 Packing: without cap in Tube

**RoHS Compliant**

TOLERANCES ARE

  
**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES  
**煜倫股份有限公司**  
[www.morethanall.com](http://www.morethanall.com)

DRAWING BY CY  
 CHECKED BY GENIUS  
 UNIT / mm SCALE 1 : 1  
 DATE  
 SIZE A4 PPROJECTION

X. ± 0.30  
 .X ± 0.25  
 .XX ± 0.15  
 .XXX ± 0.05  
 ANG ±

照片框

**ORDER INFORMATION**

**PWMT-PDXK-1X08-LF**  
 SERIES LEADFREE  
 08 WAY  
 KEY  
 NON POST  
 DIP 180°  
 MALE

DESCRIPTION: