



BOM:

8	公頭護蓋	PE(高密度)	透明	1
7	塑膠下蓋(新模)	ABS, UL94 V-0	SEE TABLE 1	1
6	塑膠上蓋(新模)	ABS, UL94 V-0	SEE TABLE 1	1
5	外殼下蓋	BRASS(H/2), T=0.30±0.02mm	吃錫鍊	1
4	外殼上蓋	BRASS(H/2), T=0.30±0.02mm	吃錫鍊	1
3	膠心(24V)	SEE TABLE 3	PANTONE Gray IC	1
2	PIN 2	BRASS(H), T=0.50±0.03mm	SEE TABLE 2	4
1	PIN 1	BRASS(H), T=0.40±0.03mm	SEE TABLE 2	4
項目	名稱	規格	電鍍(或顏色)	數量備註

PWUB-MS05Vxx-044A-LF
LEADFREE
GE: GREY
BK: BLACK

TABLE 1:

COLOR
灰色
黑色

NOTE: All materials conform ROHS standard.
ELECTRICAL CHARACTERISTICS:
RATINGS: 3.0A
CONTACT RESISTANCE:
30mΩ Max.(Initial)
400mΩ Max.(After life test)
INSULATION RESISTANCE: 1000MΩ Min
DIELECTRIC STRENGTH: 750V AC/1 minute.
MECHANICAL INSERTION FORCE: 6.6kgf MAX
WITHDRAWAL FORCE: 1.0kgf MIN

MORE THAN ALL
CONNECTORS
ASSEMBLIES

PART NO. PWUB-MS05Vxx-044A

DWG NO. PWUB-MS05Vxx-044A

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2
.XX ±
.XXX ±
AWG

DESCRIPTION:

AREA

REVISIONS

HK

DATE

煜倫股份有限公司