



BOM:

項目	名稱	規格	電鍍(或顏色)	數量備註
8	公頭護蓋	PE(高密度)	透明	1
7	塑膠下蓋(新模)	ABS, UL94 V-0	SEE TABLE 1	1
6	塑膠上蓋(新模)	ABS, UL94 V-0	SEE TABLE 1	1
5	外殼下蓋	BRASS(H/2), T=0.30±0.02mm	吃錫鍊	1
4	外殼上蓋	BRASS(H/2), T=0.30±0.02mm	吃錫鍊	1
3	膠心(24V)	SEE TABLE 3	RED(032C)	1
2	PIN 2	BRASS(H), T=0.50±0.03mm	SEE TABLE 2	4
1	PIN 1	BRASS(H), T=0.40±0.03mm	SEE TABLE 2	4

組合圖

PWUB-MS24Vxx-044A-LF
 LEADFREE
 GE:GREY
 BK:BLACK

RoHS Compliant

NOTE: All materials conform ROHS standard.
 ELECTRICAL CHARACTERISTICS:
 RATINGS:3.0A
 CONTACT RESISTANCE:
 30mΩ Max.(Initial)
 400mΩ Max.(After life test)
 INSULATION RESISTANCE:1000MΩ Min
 DIELECTRIC STRENGTH:750V AC/1 minute.
 MECHANICAL:INSERTION FORCE:6.6kgf MAX
 WITHDRAWAL FORCE:1.0kgf MIN



煜倫股份有限公司

PART NO. PWUB-MS24Vxx-044A

DWG NO. PWUB-MS24Vxx-044A

FILE NO.

CHECKED BY CY

DRAWING BY

UNIT / mm

SCALE 1:1

PROJECTION

TOLERANCES ARE
 X ±
 .X ±
 .XX ±
 .XXX ±
 ANG

DESCRIPTION:		
AREA	REVISIONS	DATE