



*****CONSTRUCTION:**

1.CABLE: * UL2725 28AWG*1PR+20AWG*6C+AB85% OD:6.5mm BLACK JACKET

*****CONNECTOR:**

2.POWER USB * POWER USB 12V PLUG SOLDERED TYPE, ASSEMBLY TYPE.
 * PIN CONTACT: BRASS WITH 30u" GOLD PLATED OVER TIN.
 * SHELL: BRASS WITH NICKEL PLATED.
 * INSULATOR: GREEN COLOR NYLON-66 UL94V-0 RATED.
 * HOOD: BLACK COLOR PLASTIC ABS.

3.TEST: * CT:2 ohm IS:5M ohm HI-POT: DC500V/3S.

4.PACKING: * PACK EACH CABLE IN A PLOY BAG AND HEAT SEALED.

PIN OUT

P1		P2
8	RED	1
6	WHITE	2
4	GREEN	3
2	BLACK	4
7	BLUE	5
5	BROWN	6
3	ORANGE	7
1	YELLOW	8
SHEEL	BRAID	SHEEL

PWUBX2-044A12V2028-M2M

	PART NO. PWUBX2-044A12V2028-M2M		RoHS Compliant		TOLERANCES ARE X. ± .X ± .XX ± .XXX ± ANG	DESCRIPTION: POWER USB PLUG TO POWER USB PLUG CABLE
	DWG NO. PWUBX2-044A12V2028-M2M		CHECKED BY CY	DRAWING BY		
焯倫股份有限公司	FILE NO.		PROJECTION		AREA	REVISIONS
	UNIT / mm	SCALE 1:1				DATE