



**040型**

- 適用線徑:  $0.3-0.5\text{mm}^2$ .
- 表面處理:  
預鍍錫膜厚  $40\mu$  以上。
- 對手件: 040型 TAB= $0.64$ 。  
插入力:  $0.3-0.8\text{KG}$ 。  
拉拔力:  $0.3-0.8\text{KG}$ 。

---

**040-TYPE.**

- Wire Range:  $0.3-0.5\text{mm}^2$ .
- Surface Treatment:  
Pre-Tin Plated Thickness  
More Than  $40\mu$ .
- Mating Part:  
040-Type TAB= $0.64$ 。  
Inserted Force:  $0.3-0.8\text{KG}$ 。  
Tensile force:  $0.3-0.8\text{KG}$ 。

材質:

主體 0.20tC5191  
彈片 0.2tC5191

Metel:

Body 0.20tC5191  
Spring 0.20tC5191

Q040-FT-20-LF  
LEADFREE  
RoHS Compliant

**MORETHANALL**  
CONNECTORS  
ASSEMBLIES

煜倫股份有限公司

PART NO. Q040-FT-20		CHECKED BY CY		TOLERANCES ARE .X $\pm$ 0.2 .XX $\pm$ 0.1 .XXX $\pm$ AWG	DESCRIP TION:		
DWG NO. Q040-FT-20		DRAWING BY					
UNIT / mm	SCALE 1:1	PROJECTION		AREA	REVISIONS	HK	DATE