



說明:

1. 表面處理:  
預鍍霧錫, 膜厚  $40\mu$ " 以上
2. 對手件:  $TAB=0.8$   
插入力:  $0.5 \sim 1.1\text{kg}$   
拉拔力:  $0.3 \sim 0.9\text{kg}$

NOTE:

1. SURFACE TREATMENT  
PRE-TUNGSTEN PLATING THICKNESS  
MORE THAN  $40\mu$ "
2. MATING PRT:  $TAB=0.8$   
INSERTED FORCE:  $0.5 \sim 1.1\text{kg}$   
TENSILE FORCE:  $0.3 \sim 0.9\text{kg}$

1	Q06035-FT-16	Phosphor bronze	Note 1	$0.5-1.3\text{mm}^2$
NO.	產品編號 Part Number	材料 Material	表面處理 Surface Treatment	線徑 Wire Range

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X.  $\pm$   
.X  $\pm$   
.XX  $\pm$   
.XXX  $\pm$   
ANG  $\pm$

PJECTION

照片框

ORDER INFORMATION

Q06035-FT-16-LF

SERIES | | LEADFREE  
16 AWG  
TERMINAL  
FEMALE

DESCRIPTION: