



說明:

1. 表面處理:

預鍍霧錫, 膜厚40u" 以上

2. 對手件: TAB=0.8

插入力: 0.5~1.1kg

拉拔力: 0.3~0.9kg

NOTE:

1. SURFACE TREATMENT

PRE-TUNGSTEN PLATING THICKNESS
MORE THAN 40u"

2. MATING PRT: TAB=0.8

INSERTED FORCE: 0.5~1.1kg

TENSILE FORCE: 0.3~0.9kg

1	Q06035-FT-20	Phosphor bronze	Note 1	0.3-0.5MM ²
NO.	產品編號 Part Number	材料 Material	表面處理 Surface Treatment	線徑 Wire Range

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1:1

DATE

SIZE A4

X. ±

.X ±

.XX ±

.XXX ±

ANG ±

PJECTION

照片框

ORDER INFORMATION

Q06035-FT-20-LF

SERIES | | LEADFREE
20 AWG
TERMINAL
FEMALE

DESCRIPTION: