



說明

- 1.預鍍錫膜厚40u"以上。
- 2.對手件:070型TAB=0.6。
- 插入力:0.3~1.0KG。
- 拉拔力:0.4~0.8KG。
- 6回拉拔力:0.2KG以上。

NOTE

- 1.Pre-Tin Plated Thickness More Than 40u".
- 2.Mating Part:070-TYPE TAB=0.6
- Inserted Force: 0.3~1.0KG.
- Tensile Force: 0.4~0.8KG.
- The Sixth Time:MoreThan 0.2KG.

2	Copper Alloys	Note 1	0.85~1.25mm ²
1	Brass	Note 1	0.85~1.25mm ²
NO.	材料 Material	表面處理 Surface Treatment	線徑 Wire Range

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION

照片框

ORDER INFORMATION

Q07035KS-FT-16-LF

SERIES | LEADFREE
16 AWG
TERMINAL
FEMALE

DESCRIPTION: 070 TYPE FEMALE TERMINAL