



NOTE :

- * Material : Nylon UL 94V-0
- * Standard Color : Black
- * Electrical rating : 600V 8A AC/DC

Series Housing
* 2-10 circuits available

KEYING LOCATION	KEYING	PART NO.	DIM. A	DIM. B	DIM. C
	X	Q08051-SHKX-1X02	5.08	19.02	23.47
		Q08051-SHKX-1X03	10.16	24.10	28.55
		Q08051-SHKX-1X04	15.24	29.18	33.63
		Q08051-SHKX-1X05	20.32	34.26	38.71
		Q08051-SHKX-1X06	25.40	39.34	43.79
		Q08051-SHKX-1X07	30.48	44.42	48.87
		Q08051-SHKX-1X08	35.56	49.50	53.95
		Q08051-SHKX-1X09	40.64	54.58	59.03
		Q08051-SHKX-1X10	45.72	59.66	64.11
			Y	Q08051-SHKY-1X02	5.08
Q08051-SHKY-1X03	10.16			24.10	28.55
Q08051-SHKY-1X04	15.24			29.18	33.63
Q08051-SHKY-1X05	20.32			34.26	38.71
Q08051-SHKY-1X06	25.40			39.34	43.79
Q08051-SHKY-1X07	30.48			44.42	48.87
Q08051-SHKY-1X08	35.56			49.50	53.95
Q08051-SHKY-1X09	40.64			54.58	59.03
Q08051-SHKY-1X10	45.72			59.66	64.11

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ± 2°

PJECTION 

照片框

ORDER INFORMATION

Q08051-SHKx-1Xxx-LF

SERIES | | LEADFREE
| | 1X02:02 WAY
| | 1X10:10 WAY
FEMALE | X:X KEY
HOUSING | Y:Y KEY

DESCRIPTION: