



SEC. A-A



SEC. B-B



SEC. C-C

NOTES:

1.插拔力:

- 1.1 插入力: 1.5~2.5 KGF
- 1.2 拔出力: 1.5~6.0 KGF

2.包裝數量: 15000 PCS/R

1.INSERTED/TENSILE FORCES:

- 1.1 INSERTED FORCE: 1.5~2.5 KGF.
- 1.2 TENSILE FORCE: 1.5~6.0 KGF.

2.PACKING Q'TY: 15000 PCS/R

Q110-FT8-20	17.5	0.3~0.5	22~20	黃銅 BRASS	鍍錫 TIN PLATING
PART NO. 編 號	PITCH 間 距	MM 線 徑	AWG WIRE SIZE	MATERIAL 材 質	FINISH 表面處理

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1:1

DATE

SIZE A4

X.±
.X±
.XX±
.XXX±
ANG±

PJECTION

照片框

ORDER INFORMATION

Q110-FT8-20-LF
SERIES LEADFREE
20~22AWG
0.8mm TAB
TERMINAL
FEMALE

DESCRIPTION: