



THICKNESS: 0.3mm
 MAT'L: BRASS TIN PLATED
 CURRENT RATING: 5A AC,DC
 VOLTAGE RATING: 250V AC,DC
 APPLICABLE WIRE RANGE: AWG#14-18
 SUITABLE TERMINAL: 0.50mm TAB
 MECHANICAL PERFORMANCE
 INSERTION FORCE: 1.0kg~1.5kg (WITH SPRING LOCKED)
 WITH DRAWAL FORCE: 5.0kg MIN (WITH SPRING LOCKED)
 2.0kg MIN(at 20th) TERMINAL AND SUITABLE TERMINAL
 SHALL BE INSERTION AND WITHDRAWAL AFTER
 REPEATED19 CYCIE (NOT SPRING LOCKED)
 0.5kg MIN (NOT SPRING LOCKED)

Q187-FT5LS-14-LF
 LEADFREE
 RoHS Compliant

MORETHANALL
 CONNECTORS
 ASSEMBLIES

PART NO. Q187-FT5LS-14

DWG NO. Q187-FT5LS-14

CHECKED BY CY

TOLERANCES ARE

DESCRIPTION:

FILE NO.

DRAWING BY

.X ± 0.2
 .XX ±
 .XXX ±
 AWG

AREA

REVISIONS

HK

DATE

煜倫股份有限公司

UNIT / mm

SCALE 1:1

PROJECTION

