



THICKNESS: 0.3mm  
 MAT'L: BRASS TIN PLATED  
 CURRENT RATING: 5A AC,DC  
 VOLTAGE RATING: 250V AC,DC  
 APPLICABLE WIRE RANGE: AWG#20-22  
 SUITABLE TERMINAL: 0.50mm TAB  
 MECHANICAL PERFORMANCE  
 INSERTION FORCE: 1.0kg~1.5kg (WITH SPRING LOCKED)  
 WITH DRAWAL FORCE: 5.0kg MIN (WITH SPRING LOCKED)  
 2.0kg MIN(at 20th) TERMINAL AND SUITABLE TERMINAL  
 SHALL BE INSERTION AND WITHDRAWAL AFTER  
 REPEATED19 CYCIE (NOT SPRING LOCKED)  
 0.5kg MIN (NOT SPRING LOCKED)

Q187-FT5LS-20-LF  
 LEADFREE

RoHS Compliant



PART NO. Q187-FT5LS-20

DWG NO. Q187-FT5LS-20

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X ± 0.2  
.XX ±  
.XXX ±  
AWG

DESCRIPTION:

AREA

REVISIONS

HK

DATE

煜倫股份有限公司