



規格 WIRE RANGE :	22-16 A.W.G (0.5-1.5mm ²)
溫度與電壓 MAXIMUM ELECTRICAL RATING :	75°C 300 VOLTS MAX.
電流 MAXIMUM ELECTRIC CURRENT :	10 AMPERE
端子材質 TERMINAL MATERIAL	BRASS
絕緣材質 INSULATION MATERIAL	VINYL
顏色 INSULATION COLOR	RED
金屬厚度 THICKNESS	0.4

公差 TOLERANCE 項目 ITEM	NEMA TAB (inch) (d2)	W ±0.20	W1 ±0.20	F ±0.30	F1 ±0.30	L ±1.00	B ±0.50	D ±0.30	C ±0.20	
尺寸 SIZE	.032X.250 (0.8X6.35)	6.60	6.35	8.00	8.20	22.00	10.00	4.00	1.70	

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X. ±

CHECKED BY GENIUS

.X ±

UNIT / mm

SCALE 1 : 1

.XXX ±

DATE

ANG ±

煜倫股份有限公司

www.morethanall.com

SIZE A4

PPOJECTION

照片框

ORDER INFORMATION

Q250-ET8V-16-LF
SERIES LEADFREE
16-22 AWG
VINYL
0.8t
TERMINAL
PIGGYBACK

DESCRIPTION: