



| | |
|--------------------------------------|---------------------------------------|
| 規格 WIRE RANGE : | 22-16 A.W.G (0.5-1.5mm ²) |
| 溫度與電壓 MAXIMUM ELECTRICAL RATING : | 75°C 300 VOLTS MAX. |
| 電流 MAXIMUM ELECTRIC CURRENT : | 10 AMPERE |
| 端子材質 TERMINAL MATERIAL | BRASS TIN PL |
| 絕緣材質 INSULATION MATERIAL | VINYL |
| 顏色 INSULATION COLOR | RED |
| 金屬厚度 THICKNESS | 0.4 |

| 公差 TOLERANCE | NEMA TAB (inch) (d2) | W ±0.2 | W1 ±0.1 | F ±0.3 | F1 ±0.3 | L ±1.0 | B ±0.5 | φD ±0.3 | φC ±0.2 |
|-----------------|----------------------------|--------|---------|--------|---------|--------|--------|---------|---------|
| 項目 ITEM | | | | | | | | | |
| 尺寸 SIZE | .032X.250 (0.8X6.35) | 6.6 | 6.35 | 8.0 | 8.2 | 22.5 | 10.5 | 3.8 | 1.7 |

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

P PROJECTION

照片框

ORDER INFORMATION

Q250-ET8VD-16-LF

SERIES | | | | LEADFREE
16-22 AWG
D TYPE
VINYL
0.8t
TERMINAL

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: