



**\*\*\*CONSTRUCTION:**

1.CABLE: \* CAT.6A SSTP (4PR/26#)+AB OD:6.2mm PVC JACKET.

**\*\*\*CONNECTORS:**

2.RJ45: \* RJ45 8P8C PLUG WITH SHELL,CONTACT: 50u GOLD PLATED.  
INSULATOR: CLEAR PC UL RATED.

SHELL: PHOSPHOR BRONZE WITH NICKELL PLATED.

\* RUBBER PAD: SILICONE COLOR BLACK.

\* METAL SCREW NUT: COPPER ALLOY FINISH NI PLATED.

\* HOUSING THERMOPLASTIC COLOR BLACK.

\* METAL COVER COPPER ALLOY FINISH NI PLATED.

\* GLAND SILICONE GOLOR GREEN.

\* CAGE THERMIPLASTIC COLOR WHITE.

\* METAL GLAND NUT: COPPER ALLOY FINISH NI PLATED.

3.TEST: \* CT:2 ohm IS:10M ohm.

\* WATERPROOF RATE: IP67.

4.PACKING: \* 1PCS PACK EACH CABLE IN A POLY BAG.

5.MATERIAL: \* MATERIAL WITH RoHS GRADE.

**PIN OUT**

CN1	PIN OUT	CN2
5	BLUE/WHITE	5
4	BLUE	4
3	GREEN/WHITE	3
6	GREEN	6
1	ORANGE/WHITE	1
2	ORANGE	2
7	BROWN/WHITE	7
8	BROWN	8
SHELL		SHELL

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±

.X ±

.XX ±

.XXX ±

ANG ±

PPOJECTION

照片框

**ORDER INFORMATION**

QLMRJX2-080826C6A-M5M-LF

SERIES

8P8C

26 AWG

CAT.6A

LEADFREE

5000mm

MALE TO MALE

DESCRIPTION: