




NO.	NAME	MATERIAL	FINISH	Q'TY
1	BARREL	C.R.S 0.30	NICKEL PLATED	1
2	RING	PBT	WH,RD,YL,BK,BL,GR	1
3	INSULATOR	PBT	WHITE	1
4	BRACKET	C.R.S 0.40	NICKEL PLATED	1
5	TERMINAL	BRASS 0.25	TIN PLATED	1

Specification:

Contact Resistance: 30m Ohm Max. At AC 100mA Max.1KHz.

Insulation Resistance: 100M Ohm Min. At 500V DC.

Rated Voltage And Current: DC 12V,2A Max.

Dielectric Withstanding Voltage: 500VAC At 60Hz For 1 Minute.

Durability (Life Test): 4000 Cycles.

Insertion Force: 0.3~3.0 Kg.

Extraction Force: 0.3~3.0 Kg.

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1


DATE

SIZE A4

TOLERANCES ARE

X.±
.X±
.XX±
.XXX±
ANG±

PPOJECTION



ORDER INFORMATION

RCA-JD13xx-02-LF

SERIES

JACK

DIP 180°

10.4+3.5mm

BK:BLACK

YL:YELLOW

RD:RED

WH:WHITE

BL:BLUE

GR:GREEN

LEADFREE

02 WAY

DESCRIPTION: