

T:1.6 Dimensions of PC board holes
Tolerance : ±0.1(Printed-top view)

| MODEL NO. | COLOR OF HOUSING |
|----------------|------------------|
| RCA-JR44MBK-02 | BLACK |
| RCA-JR44MYL-02 | YELLOW |
| RCA-JR44MRD-02 | RED |
| RCA-JR44MWH-02 | WHITE |

| Model No. | RCA-JR44Mxx-02 |
|-----------|----------------|
| Schematic | |

| LTR | PART NAME | QTY | MATERIAL | REMARK |
|-----|---------------|-----|----------|--------------------|
| 4 | SHIELD | 1 | SPCC | MB:Cu Ni PLATED |
| 3 | TERMINAL | 1 | BRASS | MB:Cu Cu/Sn PLATED |
| 2 | OUTER CONTACT | 1 | BRASS | MB:Cu Cu/Sn PLATED |
| 1 | HOUSING | 1 | PBT | |

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.3

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

PPOJECTION



ORDER INFORMATION

RCA-JR44Mxx-02-LF

SERIES JACK
DIP 90°
4.0+4.5mm

LEADFREE
02 WAY
BK:BLACK
WH:WHITE
METAL FOOT

DESCRIPTION: PIN JACK

www.morethanall.com