

T:1.6 Dimensions of PC board holes

Tolerance : ±0.05(Printed-top view)

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.3

| | S JACK | PIN JACK | |
|-----------|--------|----------|--------|
| SCHEMATIC | | | |
| COLOR | BLACK | WASHER | YELLOW |
| | | HOUSING | BLACK |

| | | | | |
|-----|----------------|-----|--------------|--------------|
| 10 | SEALED PLATE | 1 | C2680 t=0.25 | Cu/Sn PLATED |
| 9 | EARTH FITTING | 1 | C2680 t=0.3 | Cu/Sn PLATED |
| 8 | EARTH FITTING | 1 | C5191 t=0.25 | Ag PLATED |
| 7 | TERMINAL | 1 | C2680 t=0.4 | Cu/Sn PLATED |
| 6 | HOUSING | 1 | PBT 4815 | UL-94V0 |
| 5 | WASHER | 1 | PBT 4815 | UL-94V0 |
| 4 | OUTER CONTACT | 1 | C2680 t=0.4 | Au PLATED |
| 3 | GROUND CONTACT | 1 | C2680 t=0.3 | Au PLATED |
| 2 | EARTH FITTING | 1 | C2680 t=0.2 | Cu/Sn PLATED |
| 1 | CENTER CONTACT | 4 | C5191 t=0.4 | Ag PLATED |
| LTR | PART NAME | QTY | MATERIAL | REMARK |

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT / mm

SCALE 1 : 1


.XXX±

DATE

ANG±

SIZE A4

P PROJECTION



ORDER INFORMATION

RCMDB1-FREYL-0204A-LF

SERIES | | | | LEADFREE
A LAYOUT
02 TO 04 WAY
YELLOW
FEMALE TO FEMALE | EAR | DIP 90°

DESCRIPTION: PIN JACK+S JACK

煜倫股份有限公司

www.morethanall.com