



WIRING DIAGRAM

P1		P2
3	—————	OPEN
4	—————	OPEN

ELECTRICAL SPECIFICATION:  
 1.100% OPEN SHORT&MISS WIRE TEST  
 2.VOLTAGE:DC 300V  
 3.INSULATOR RESISTANCE:2M OHM MIN  
 4.CONDUCTIVE RESISTANCE:5 OHM MAX

NO.	NAME	DESCRIPTION	QTY
①	CONNECTOR	6P2C PLUG;PIN GOLD-FLASH PLATED	1PC
②	CABLE	NO-UL 26AWG*2C FLAT CABLE ;OD:2.5*5.0MM;METAL GREY JACKET ;L=1200MM	1PC

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X.±  
 .X±  
 .XX±  
 .XXX±  
 ANG±

P PROJECTION

照片框

ORDER INFORMATION

RJX1-620026MG-M1M2-LF  
 SERIES | 6P2C | | | | LEADFREE  
 | | | | | 1200mm  
 | | | | | MALE  
 | | | | | GRAY  
 | | | | | METAL  
 | | | | | 26AWG

DESCRIPTION: