





### Circuit Diagram



**Performance:**  
Meets C3 Standard.

**Materials:**  
Body : Fireproof ABS UL-94V0  
Jack : 6P6C 6 micro inches gold plated  
(Through-Pin)

**Electrical Specifications:**  
Insulation Resistance : 500M ohms (min.)  
Contact Resistance : 20m ohms (max.)  
Current Rating : 1.5 Amps .  
DC Resistance : 0.1 ohms (max.)  
Withstanding Voltage : 1000 VAC RMS @ 60Hz / 1 min.

**Mechanical Specifications:**  
Jack Insertion Cycle : Over 2000 Cycles (min.)

Operation Temperature : -40 °C ~ +70 °C

**RoHS Compliant**

TOLERANCES ARE


**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY	CY
CHECKED BY	GENIUS
UNIT / mm	SCALE 1 : 1
DATE	
SIZE	A4
PPOJECTION	

X, ±
.X ±
.XX ±
.XXX ±
ANG ±



**ORDER INFORMATION**

RJX2-FSC3PN28WH-0606-LF  
 SERIES | WHITE | 6P6C | LEADFREE  
 FEMALE TO FEMALE 180° | PANEL | LONG 28mm  
 C3

DESCRIPTION: C3 INLINE COUPLER UTP 6u