



MATERIALS

- 1. HOUSING: NYLON 9T (UL 94V-0), BLACK.
- 2. TERMINAL: PHOSPHOR BRONZE. (T=0.50mm)

SPECIFICATION

- 1. CURRENT RATING: 2 AWP. MAX.
- 2. DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC R.M.S. FOR ONE MINUTE.
- 3. INSULATION RESISTANCE: 1000M Ω MIN. AT 500V DC.
- 4. CONTACT RESISTANCE: 30M Ω MAX.
- 5. OPERATING TEMPERATURE: -40°C TO +85°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1:1

DATE

SIZE A4

X. \pm
.X \pm
.XX \pm
.XXX \pm
ANG \pm

P PROJECTION

照片框

ORDER INFORMATION

S-D093121-4X30-LF
SERIES | 120 WAY | LEADFREE
DIP 12.1mm
HIGH 9.3mm
DIP 180°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: