



PCB LAYOUT

SPECIFICATIONS

- * Current Rating : 1 Amps
- * Insulator resistance: 5000 Megohms min.
- * Dielectric withstanding: AC 500 V
- * Operating Temperature: -40° – $+105^{\circ}$ C
- * Max Processing Temp: 230° for 30~60 seconds
(260° for 10 seconds)
- * Contact Material: Phosphor bronze
- * Housing: L.C.P. (UL 94 V-0)

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ± 0.20

.X ± 0.15

.XX ± 0.10

.XXX ± 0.05

ANG $\pm$

PPOJECTION

照片框

ORDER INFORMATION

S-V24XC-1XxxL-LF
SERIES | | | | LEADFREE
180° SMT | | | | L TYPE
HIGH 2.4mm | | | | 1X02:02 WAY
MYLAR | | | | 1X50:50 WAY
NON POST

DESCRIPTION: 2.0mm Single Row(H=2.4mm) SMD Type