



PCB LAYOUT

SPECIFICATIONS

- * Current Rating : 1 Amps
- * Insulator resistance: 5000 Megohms min.
- * Dielectric withstanding: AC 500 V
- * Operating Temperature: -40°-+105°C
- * Max Processing Temp: 230° for 30~60 seconds
(260° for 10 seconds)
- * Contact Material: Phosphor bronze
- * Housing: L.C.P. (UL 94 V-0)

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司

DRAWING BY CY

X. ± 0.20

CHECKED BY GENIUS

.X ± 0.15

UNIT / mm

SCALE 1 : 1

.XX ± 0.10

.XXX ± 0.05

DATE

ANG ±

www.morethanall.com

SIZE A4

PJECTION

照片框

ORDER INFORMATION

S-V24XC-1XxxR-LF
 SERIES | | | | LEADFREE
 | | | | R TYPE
 | | | | 1X02:02 WAY
 180° SMT | | | | 1X50:50 WAY
 HIGH 2.4mm | MYLAR
 NON POST

DESCRIPTION: 2.0mm Single Row(H=2.4mm) SMD Type