



Recommended P.C.B Layout

**MATERIAL**

Contact Pin : Phosphor Bronze  
 Insulator : NY6T UL94-V0

**SPECIFICATION**

Current Rate : 3 AMP PER PIN(26AWG)  
 Insulation Resistance : 5000mΩMin.  
 Contact Resistance : 20mΩMax.  
 Dielectric Voltage : AC 500V for one minute  
 Operation Temperature: -40°C to +105°C

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

DRAWING BY CY  
 CHECKED BY GENIUS  
 UNIT / mm SCALE 1 : 1  
 DATE

X. ±  
 .X ± 0.30  
 .XX ± 0.20  
 .XXX ±  
 ANG ± 3°

照片框

**ORDER INFORMATION**

S-V45X-2X14-LF  
 SERIES | LEADFREE  
 | 28 WAY  
 | NON POST  
 | HIGH 4.5mm  
 | 180°SMT

煜倫股份有限公司

www.morethanall.com

SIZE A4 PPROJECTION

DESCRIPTION: FEMALE HEADER 2.0\*2.0mm STRAIGHT TYPE, DUAL ROWS HEIGHT 4.3mm