



### Technical Data :

**Insulator Material:** High Temperature Thermoplastic, UL 94V-0  
**Contact :** stamped and formed, Phosphor Bronze  
**Plating:** Selective gold flash plated  
**Current Rating :** 1 Amp  
**Contact resistance:** 20 milliohms Max.  
**Insulator resistance :** 1000 Megohms min.  
**Dielectric withstanding :** AC 500V for 1 Minute.  
**Operating Temperature:** -55°C to +105°C.  
**Max. processing Temp:** 230°C for 30-60 seconds.  
 260°C for 10 seconds.  
**Packing:** Tape & Reel  
**Mates with :** Pitch 2.0mm, 0.50mm male header

**RoHS Compliant**

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ± 0.30

.X ± 0.25

.XX ± 0.15

.XXX ± 0.05

ANG ±

PJECTION

照片框

**ORDER INFORMATION**

S-W63X-2X10-LF  
 SERIES | LEADFREE  
 20 WAY  
 NON POST  
 LONG 6.35mm  
 90°SMT

DESCRIPTION: female header 2.0mm pitch H6.35 Dip 180 Type