



技术要求:

成品线必须100%导通通过,不可有短路.断路及
间隙性开路等不良现象.

备注: 所有材料都为环保料

WIRE CHART			
CON1		CON2	
PIN 1	↘	PIN 1	↙
PIN 4	↗	PIN 4	↖
PIN 7	↘	PIN 7	↙
PIN 2	—	PIN 2	—
PIN 3	—	PIN 3	—
PIN 5	—	PIN 5	—
PIN 6	—	PIN 6	—

③	45P 黑色 PVC (低毒)	1
②	8.con Serial ATA 26AWG E119932 AWG 2725 L=480mm (低毒)	1
①	SATA7P/180° 插头 黑色 (低毒)	2
NO.	DESCRIPTION	Q'TY

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

TOLERANCES ARE

X. ±

.X ±

.XX ±

.XXX ±

ANG ±

PPOJECTION

照片框

ORDER INFORMATION

SATAX2-070726-F1M33-LF

SERIES

LEADFREE

1330mm

FEMALE TO FEMALE

26 AWG

7 PIN TO 7 PIN

DESCRIPTION: