



**PIN ASSIGNMENT**

Conn.1	Conn.2	Signal
1	1	GND
2	2	A+
3	3	A-
4	4	GND
5	5	B-
6	6	B+
7	7	GND

**ELECTRONIC TEST:**

- 1.ALL CABLE 100% TEST,OPEN ,SHORT,MISSWIRE
- 2.RESISTANCE:2 ohm max
- 3.I.RESISTANCE:10M ohm min
- 4.HI--POT:300V DC/10ms
- 5.DIMENSIONS MARK "▼" SHOULD BE CHECKED;

5	G101-4500-000	45P PVC COLOR:BLACK	3.5/1K	Kg
4	G101-3500-000	35P PVC COLOR:BLACK	1.5/1K	Kg
3	G043-0110-000	SATA 7P SHORT LATCH	2	pcs
2	G012-2608-030	SERIAL ATA CABLE E119932-T 26AWG OD:2.20*7.80±0.20mm	N/A	mm
1	GSS10-0703-02	S-ATA-7P BLACK PIN GOLD FLASH W/LATCH 3u"	2	pcs
NO.	PART NO.	DESCRIPTION	Q'TY	UNIT

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ± 0.30  
.XX ± 0.20  
.XXX ± 0.10  
ANG ±

P PROJECTION

照片框

**ORDER INFORMATION**

SATAX2-7R7S26-F14C7-LF

SERIES

LEADFREE

147mm

FEMALE TO FEMALE

26AWG

7 PIN 90° TO 7 PIN 180°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: