



WIRE CHART:

CONN1		CONN2
1	GND	1
2	A -	2
3	A +	3
4	GND	4
5	B -	5
6	B +	6
7	GND	7

ELECTRONIC TEST CONDITION:
 100% OPEN SHORT MISWIRE TEST
 CONDUCTIVE RESISTANCE: 5 OHM/MAX
 INSULATION RESISTANCE: 10M OHM MIN
 AT DC 300V PER MILISECOND

Material requirements: ROHS

④	PVC 45P BLACK ROHS	10G
③	SATA 7P FEMALE (TER G/F PBT BLACK) ROHS	1PCS
②	SATA 7P FEMALE WITH LATCH (TER G/F PBT BLACK) ROHS	1PCS
①	UL2725 26AWG*2C*2+AL+4D OD: 2.2*7.8mm RED ROHS	1PCS
NO.	DESCRIPTION	Q'TY

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1:1

DATE

SIZE A4

X. ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

PJECTION

照片框

ORDER INFORMATION

SATAX2-7R7S26-F30C-LF

SERIES

LEADFREE

300mm

FEMALE TO FEMALE

26AWG

7 PIN 90° TO 7 PIN 180°

DESCRIPTION: SATA7P/7P 90/180度 L=300MM