

PCB HOLE PATTEN

MATERIAL:

- A.INSULATOR:PC(94V 2)&GLASS FIBER
- B.CONTACT:BRONZE
- C.CONTACT PLATED:TIN PLATED

SPECIFICATION:

- A.CURRENT RATE:3A/250V AC

CINTACT RESISTANCE:

- A.(BRONZE)11.5MΩ AT 2V DC 100mA
- B.(PHOSPOR BRONZE)10.9MΩ AT 2V DC 100mA
- C.INSULATOR RESISTANCE:1.5GΩ AT 500V DC 1Min
- D.dielectric withstanding:1000Vvar 1Min
- PHOSPHER BRONZE PART NO CW 30314 2 PHOSPHER
- PHOSPHER PART NO CW 30314 2, SCP DHR 1

注:1.有@ 的符號為品管重點測量尺寸
2.符合本公司環境管理物質標準

2.	90°端子	銅	鍍錫
1.	SCART反向小膠芯	PC	
編號NO.	名 稱 DESCRIPTION	材 質 MATERIAL	備 註 REMARK

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1


DATE

SIZE A4 PPROJECTION

X, ±
.X ± 0.30
.XX ± 0.25
.XXX ± 0.20
ANG ± 0.25°

照片框

ORDER INFORMATION



DESCRIPTION: 電腦頭母90度機板式 無耳 (黑)