



**NOTE:**

1. HOUSE MATERIAL: PBT+30%G.F 94L V-0 COLOR: BLACK.
2. TERMINAL MATERIAL: COPPER ALLOY, THICKNESS =  $0.30 \pm 0.02$ .  
FINISH: GOLD PLATE ON CONTACT AREA, TIN PLATE ON SOLDER TAIL, NICKEL ON ALL SURFACE
3. GROUND SPRING PIN: COPPER ALLOY, THICKNESS =  $0.25 \pm 0.02$ .  
FINISH: TIN OR GOLD PLATE ON ALL SURFACE, NICKEL ON ALL SURFACE.
4. GROUND PIN: COPPER ALLOY, THICKNESS =  $0.25 \pm 0.02$ mm.  
FINISH: TIN OR GOLD PLATE ON ALL SURFACE, NICKEL ON ALL SURFACE
5. OPERATING TEMPERATURE:  $-40^{\circ}\text{C} \sim +80^{\circ}\text{C}$ .
6. CURRENT RATING: 1 Amp MAX.
7. ●: MANUFACTURER INSPECTION.
8. ◆: Q.C INSPECTION.

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

X. ±

CHECKED BY GENIUS

.X ±

UNIT / mm

SCALE 1 : 1

.XX ±

DATE

.XXX ±

ANG ±

SIZE A4

PJECTION

照片框

**ORDER INFORMATION**

SCFA-R33BCH-08-LF

SERIES | | | | LEADFREE  
| | | | 08 WAY  
| | | | CENTER HIGH  
| | | | OPEN/SWITCH  
| | | | HIGH 3.3mm  
| | | | DIP 90°

DESCRIPTION:

煜倫股份有限公司

www.morethanall.com