

RECOMMENDED PCB LAYOUT

NOTE:

1. MATERIAL AND FINISH:
 - A. HOUSING: PBT UL 94-V0 COLOR: BLACK.
 - B. CONTACT: PHOSPHOR BRONZE. SELECTIVE PLATING AU OVER 50 μ NI MIN UNDERPLAT SN ON TAIL ZONE(RoHS).
 - C. SWITCH: BRASS .SELECTIVE PLATING AU OVER 50 μ NI MIN UNDERPLAT SN ON TAIL ZONE(RoHS).
2. READING CONTACT:

POSITION: ACCORDING TO ISO 07816-2 C1-C8.

CONTACT FORCE: 30-50 GRAM.
3. CARD INSERTION SPECIFICATION
 - A. CARD INSERTION DEPTH: 35.5 MM.
 - B. CARD THICKNESS=0.7-0.8 MM.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT/mm SCALE 1:1

DATE

SIZE A4


X, \pm
X \pm 0.25
.XX \pm 0.15
.XXX \pm 0.10
ANG \pm 2°

P PROJECTION

照片框

ORDER INFORMATION

SCFA-R62A-08-LF



DESCRIPTION: SMART CARD CONNECTOR