



**NOTE:**

- 1.Card insertion specification
  - A. Card insertion depth:35.3mm.
  - B.Card thickness=0.7-0.8 mm.
- 2.Reading contact:
  - Position:According to ISO 07816-2 C1-C8.
  - Contact force:30-50 gram.
- 3.Material and finish:
  - A. Housing: PBT UL 94-V0 Color: Black.
  - B.Contact:Phosphor bronze.selective plating Au over 50u" Ni min underplat Tin on tail zone.
  - C.Switch:Phosphor bronze.selective plating Au over 50u" Ni min underplat Tin on tail zone.

Through Hole Mounting

**RoHS Compliant**

TOLERANCES ARE



DRAWING BY CY  
 CHECKED BY GENIUS  
 UNIT / mm SCALE 1 : 1  
 DATE  
 SIZE A4

X, ±  
 .X ±  
 .XX ±  
 .XXX ±  
 ANG ±

煜倫股份有限公司

www.morethanall.com

PJECTION



**ORDER INFORMATION**

SCFA-R65x-08-LF  
 SERIES | LEADFREE  
 | 08 WAY  
 DIP 90° | A:CLOSED/SWITCH  
 | B:OPEN/SWITCH  
 HIGH 6.50mm

DESCRIPTION: