



NOTES:

- General Characteristics
Mounting System: SMT
Durability: 3,000 cycles min.
- Material and Finish:
Insulation material: High Temperature Plastic (UL94V-0)
Contact material: Copper Alloy
Contact Finish: See Order Information Selectivity.
- Electrical Characteristics
Number of contacts: 6 Position & 8 Position
Contact resistance: 50 mΩ typical, 100 mΩ max.
Insulation resistance: >1000 megaohms /500 VDC
Operation: Normally open.
- Environmental Characteristics
Operating temperature: -40°C~+85°C
Operating humidity: 10%~95%RH
Storage temperature: -40°C, +85°C
Storage humidity: 10%~95%RH
Thermal shock: -40°C~+85°C, 5 cycles
Damp Heat: 40°C, 90%RH, 10 days.
Salt-mist: 35°C, 5%, NaCl, 24 Hrs.

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY
CHECKED BY GENIUS
UNIT / mm SCALE 1 : 1
DATE
SIZE A4 PPROJECTION

TOLERANCES ARE

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ±

照片框

ORDER INFORMATION

SCP-W14PBA25-08-LF
SERIES | | | | LEADFREE
| | | | 08WAY
| | | | EAR/POST 2.5mm
| | | | SWITCH OPEN
90°SMT | | | | POST
| | | | POST TO POST 14.0mm

DESCRIPTION: