


RECOMMENDED P.C.B LAYOUT
COMPONENT SIDE (TOLERANCE ±0.05)

MATERIALS

HOUSING: HI-TEMP. PLASTIC (UL 94V-0), BLACK
 TERMINAL: PHOSPHOR BRONZE, GOLD PLATED ON
 CONTACT AREA TIN PLATING ON SOLDER TAIL
 SHELL: STAINLESS STEEL SMT SOLDER AREA GOLD PLATED

SPECIFICATION

CURRENT RATING: 1 AMP MAX
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -25°C ~ +85°C



CONTACT NO.	ASSIGNMENT	DESCRIPTION
C1	Vcc	Power Voltage
C2	RST	Reset Signal
C3	CLK	Clock Signal
C4	RFU	Reserve for future use
C5	GND	Power and Signal Ground
C6	Vpp	Programming Voltage
C7	I/O	Serial Data input/output
C8	RFU	Reserve for future use

ELECTRIC FUNCTION	DETECT SWITCH
WITHOUT CARD	OPEN
CARD INSERTED	CLOSED



SWITCH OPERATION DIAGRAM

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
 X ± 0.30
 .XX ± 0.20
 .XXX ± 0.10
 ANG ± 3°

P PROJECTION

照片框

ORDER INFORMATION

SCP-W20EB17-06-LF
 SERIES | | | LEADFREE
 90°SMT | | | 06WAY
 20mm | | | EAR TO PAD 17mm
 | | | OPEN TYPE
 | | | EAR

DESCRIPTION: SIM CARD, H=2.20 PCB MOUNT, SMT WITHOUT POST