



MATERIALS

HOUSING: HI-TEMP. PLASTIC (UL 94V-0), BLACK
 TERMINAL: PHOSPHOR BRONZE, GOLD PLATED ON CONTACT
 AREA TIN PLATING ON SOLDER TAIL

SPECIFICATION

CURRENT RATING: 0.5 AMP MAX
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -40°C~+85°C

PIN NO.	NAME
C1	Vcc
C2	RST
C3	CLK
C5	GND
C6	Vpp
C7	I/O

CONNECTOR PIN NO.	DESCRIPTION
C1	VCC:Power Voltage
C2	RST:Reset signal
C3	CLK:Clocking signal
C5	GND:Power and Signal Ground
C6	VPP:Porgraming Voltage
C7	I/O:Serial date input/output

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES
煜倫股份有限公司
www.morethanall.com

DRAWING BY CY		X, ±
CHECKED BY GENIUS		.X ± 0.30
UNIT / mm	SCALE 1 : 1	.XX ± 0.20
DATE		.XXX ± 0.10
SIZE A4	PJECTION	ANG ±



ORDER INFORMATION

SCV-W2525X-06-LF
 SERIES | | | LEADFREE
 | | | 06WAY
 | | | NON POST
 | | | BODY HIGH 2.5mm
 | | | PAD TO PAD 25.54mm
 90°SMT

DESCRIPTION: SIM CARD, 6PIN, PCB MOUNT, SMT, HINGE TYPE