



**MATERIALS**

HOUSING: HI-TEMP. PLASTIC (UL 94V-0)  
TERMINAL: COPPER ALLOY, GOLD PLATED

**SPECIFICATION**

CURRENT RATING: 0.5 AMP MAX  
DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE  
CONTACT RESISTANCE: 30m OHMS MAX  
INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V  
OPERATION TEMPERATURE: -40°C~+85°C

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ± 0.40

.X ± 0.30

.XX ± 0.20

.XXX ± 0.10

ANG ±

PPOJECTION

照片框

**ORDER INFORMATION**

SCX-W0815X-06-LF  
SERIES | | | LEADFREE  
| | | 06WAY  
90°SMT | | NON POST  
| | HIGH 1.5mm  
PAD TO PAD 8.10mm

DESCRIPTION: SIM CARD, 6PIN, PCB MOUNT, SMT, ALL PLASTIC, H=1.50mm, FEMALE