



NOTES:

1, GENERAL TOLERANCE IS ± 0.1 , $\pm 0^\circ 30'$.

2, NO DAMAGE AFTER ASSEMBLE.

3, MATERIAL: HOUSING=LCP / UL94V-0
LEAD FREE COLOR: NATURAL=3.3V DRAM, BLACK=X.XV DRAM.

CONTACT=PHOS-BRONZE(t=0.2)

SOLDER TAB=PHOS-BRONZE(t=0.3)

4,FINISH: CONTACT GOLD PLATING ON CONTACT AREA
LEAD FREE (PLEASE REFER TO PART NUMBER)
(100u" TIN OR GOLD FLASH)LEAD ON SOLDER AREA
40u" NICKLE UNDERPLATED FOR ENTIRE CONTACT

SOLDER TAB=120u" TIN LEAD 90/10

40u" NICKEL UNDERPLATED FOR ENTIRE TAB.

5,PACKAGING SPEC. PK-500-00

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, \pm
.X \pm
.XX \pm
.XXX \pm
ANG \pm

P PROJECTION

照片框

ORDER INFORMATION

SDM8-W52Vxx-6084-LF

SERIES | | LEADFREE
60+84WAY

V33:3.3V
V50:5.0V
HIGH 5.2mm
90°SMT

DESCRIPTION: S.O.DIMM SOCKET 5.2 144 POS (反) ASS'Y (LEAD FREE) CUSTOMER DRAWING