

RECOMMENDED P.C.B LAYOUT
TOLERANCE ±0.05mm
TOP VIEW

MATERIALS

1. HOUSING : THERMOPLASTIC (UL94V-0) BLACK
2. TERMINAL : COPPER ALLOY (t=0.50mm)
GOLD PLATED OVER NICKEL

SPECIFICATION

1. CURRENT RATING : 1 A MAX.
2. DIELECTRIC WITHSTANDING VOLTAGE :
800V AC R.M.S. FOR ONE MINUTE.
3. INSULATION RESISTANCE : 5000MΩ MIN.
AT 500V DC.
4. CONTACT RESISTANCE : 30mΩ MAX.
5. OPERATING TEMPERATURE : -40°C TO +85°C.

SE-D093119-4X30-LF
LEADFREE

RoHS Compliant



PART NO. SE-D0931 19-4X30

DWG NO. SE-D0931 19-4X30

FILE NO.

CHECKED BY CY

DRAWING BY

TOLERANCES ARE

.X ± 0.2
.XX ±
.XXX ±
AWG

DESCRIPTION:


4Rx30
2.00PH FEMALE HEADER 180°
SOLDER TAIL LENGTH 11.99mm ROHS

煜倫股份有限公司

UNIT / mm

SCALE 1:1

PROJECTION



AREA

REVISIONS

HK

DATE