

**SPECIFICATION**

- 1.RATING:DC 50V 0.3A
- 2.CONTACT RESISTANCE: 30Mohm MAX (INITIAL)
- 3.INSULATION RESISTANCE: 100Mohm AT 500VDC
4. WITHSTAND VOL TAGE: AC 500V FOR 1 MIN
5. OPERATION FORCE: REFER ATTACH SPECIFICATION
6. SWITCHING LIFE: 10000 CYCLES (15-18C/M UNL OAOING)

G	STEEL BALL	STAINLESS STEEL	2	NATURAL
F	CONTACT(CLIP)	P.B.S STRIP	2	AG PLATED
E	SPRING	STEEL STRIP	1	NI PLATED OR NATURAL
D	TERMAINAL	BRASS STRIP	10	AG PLATED
C	TERMAINALBASE	PHENOL IC RESIN	1	NATURAL
B	FRAME	STEEL STRIP	1	NI PLATED
A	KNOB	POM	1	BLACK
ITEM	PART	MATERIAL	QTY	REMARKS

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

X ± 0.40

CHECKED BY GENIUS

.X ± 0.30

UNIT / mm

SCALE 1 : 1

.XX ± 0.25

DATE

.XXX ± 0.20

ANG ± 1°

照片框

煜倫股份有限公司

www.morethanall.com


SIZE A4

P PROJECTION

**ORDER INFORMATION**

**SLSW20-DM060-2X05E2P-LF**

SERIES



DESCRIPTION: SLIDE SWITCH