



类型	滑动开关	品名	SLSW25-RX-2X03
1. 功能规格			
1.1 额定电压	DC6V	1.6 自由位置 (FP)	
1.2 额定电流	0.3A	1.7 动作位置 (OP)	
1.3 接触电阻 (CR)	≤70m (初始值)	1.8 行程 (PT)	2.0 ± 0.2mm
1.4 操作力 (OF)	250 ± 150gf	1.9 回弹力 (RF)	
1.5 灵敏度 (BT)		1.10 总行程 (TT)	
2. 可靠度参数			
2.1 机械寿命	10,000 cycles	2.5 焊接工艺	手工焊、波峰焊
2.2 电气寿命	10,000 cycles	2.6 适用温度	-15°C - +65°C
2.3 绝缘电阻	≥100MΩ DC500V	2.7 适用湿度	< 85%RH
2.4 耐压强度	AC500V 1 minute	2.8	

RoHS Compliant

TOLERANCES ARE



DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

P PROJECTION

照片框

ORDER INFORMATION

SLSW25-RX-2X03-LF

SERIES | LEADFREE  
06 WAY  
NON POST  
DIP 90°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: