



P.C.B LAND PATTERN

SPECIFICATIONS

| | |
|---------------------------------|--------------------|
| Rating | 0.3A 6V DC |
| Insulation Resistance | 50MΩ Min. |
| Dielectric Withstanding Voltage | AC 250 V(50Hz)1min |
| Contact Resistance | 100mΩ Max. |
| Operating Force | 200 ± 50gf |
| Operating Life | 10,000 cycles |

| NO. | DESCRIPTION | QTY | MATERIAL | PLATING |
|-----|-------------|-----|-----------------|-----------|
| E | TERMINAL | 6 | PHOSPHOR BRONZE | Ag plated |
| D | CLIP | 2 | BEUC | Ag plated |
| C | COVER | 1 | SUS | |
| B | CASE | 1 | PA6T | Black |
| A | SLIDER | 1 | PA46 | Black |

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

Up to 5 ±0.2
Above 5 ~ 30 ±0.3
Above 30 ~ 50 ±0.4
Above 50 ±0.5
Angle ±0.3

照片框

ORDER INFORMATION

SLSW25-WX020-2X03-LF

SERIES

LEADFREE

06 WAY

HANDLE HIGH 2.0mm

NON POST

90°SMT

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: SMT SLIDE SWICTH