


P.C. MOUNTING



MODEL NO.	POS.1	POS.2	POS.3
6011	ON	NONE	ON
Term. Comm.	2 - 1	OPEN	2 - 3
SCHEMATIC			

**SPECIFICATION**

- Rating:** 1A @ 250V AC  
3A @120V AC or 28V DC.
- Insulation resistance:** 1,000MΩ Min.
- Contact resistance:** 50mΩ Max.(Initial)
- Mechanical life:** 20,000 make-and-break Cycles.
- Dielectric strength:** 1,000V RMS @ sea level.
- Operating temperature:** -40°C ~ +80°C.
- Breaking capacity:** Silver: 1A 250V AC : Gold 100mA 30V DC : With Resistive load.
- Minimum load:** Silver : 100mA 10V DC : Gold : 10mA 50mV.
- Soldering temperature:** 250°C Max for 3 Sec.

**MATERIAL**

- Case:** Nylon, white.
- Actuator:** Nylon, black.
- Housing:** Nylon, black.
- Contact:** Silver plated copper alloy.
- Terminals:** Silver plated copper alloy.

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY		X. ± .X ± .XX ± .XXX ± ANG ±
CHECKED BY GENIUS		
UNIT / mm	SCALE 1 : 1	
DATE		
SIZE A4	PJECTION	

照片框

ORDER INFORMATION

SLSW26-DX-1X03-LF  
 SERIES | LEADFREE  
 | 03 WAY  
 | NON POST  
 | DIP 180°

DESCRIPTION: