



Model No.	Switching Position		
FSP-1	ON	NONE	ON
FSP-3	ON	OFF	ON
Term. Comm.	2-1	OPEN	2-3

- SPECIFICATIONS:**
- MOVABLE CONTACT: Copper alloy, silver plated
 - TERMINALS: Copper alloy, silver plated.
 - RATING: 3Amps with resistive load @ 125VAC or 28VDC
1.5Amps with resistive load @ 250VAC
 - CONTACT RESISTANCE: 20m-ohms max. initial
 - INSULATION RESISTANCE: 1,000M-ohms min.
 - DIELECTRIC STRENGTH: 1,500V RMS @ sea level
 - ELECTRICAL LIFE: 30,000 make and break cycles at full load
 - OPERATING TEMPERATURE: -30°C to 85°C

RoHS Compliant

TOLERANCES ARE
 X.±
 .X±
 .XX±
 .XXX±
 ANG±

照片框

ORDER INFORMATION

SLSW26-UX29-3X01-LF
 SERIES | LEADFREE
 | 03 WAY
 | KNOB LENGTH 2.9mm
 | NON POST
 U TYPE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY
 CHECKED BY GENIUS
 UNIT / mm SCALE 1:1
 DATE
 SIZE A4 PROJECTION

DESCRIPTION: **SUB-MIN SLIDE SWITCH**