



Model No.	POS.1	POS.2	POS.3
5MD1	ON	NONE	ON
Term. Comm.	2-1,5-4	N/A	2-3,5-6
SCHEMATIC			

SWITCH FUNCTION

SPECIFICATIONS

MECHANICAL LIFE: 30,000 make-and-break cycles.
CONTACT RESISTANCE: 10mΩ max. initial @ 2-4VDC
 100mA for both silver and gold plated contacts.
INSULATION RESISTANCE: 1,000MΩ min.
DIELECTRIC STRENGTH: 1,000 V RMS@sea level.
OPERATING TEMPERATURE: -30°C to 85°C.

MATERIALS

CASE: Dially phthalate (DAP) (UL94v-0).
ACTUATOR: Nylon, black std.
HOUSING: Stainless Steel.
CONTACT: Silver or gold plated.
TERMINAL SEAL: Epoxy.
RoHS: 2002/95/EC

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4 PPROJECTION

X, ±
 .X ± 0.40
 .XX ± 0.25
 .XXX ±
 ANG ± 5°

照片框

ORDER INFORMATION

SLSW47-DZ119-2X03-LF

SERIES | LEADFREE
 06 WAY
 KNOB LENGTH 11.96mm
 CLIP
 DIP 180°

DESCRIPTION: Slide Switches