



P.C. MOUNTING

| Model No. | POS.1 | POS.2 | POS.3 |
|-------------|-------|-------|-------|
| | | | |
| 6MS1 | ON | NONE | ON |
| Term. Comm. | 2-1 | OPEN | 2-3 |
| SCHEMATIC | | | |

SWITCH FUNCTION

SLSW51-R02-1X03-LF
LEADFREE
RoHS Compliant

SPECIFICATIONS

CONTACT RESISTANCE: 50 mΩ max. initial .
MECHANICAL LIFE : 20,000 make-and-break cycles.
INSULATION RESISTANCE: 1,000 MΩ min.
DIELECTRIC STRENGTH: 1,000 Vrms min.@sea level.
OPERATING TEMPERATURE: -40°C to 80°C.

MATERIALS

CASE - PBT, White. (B)
ACTUATOR - PBT, black .
HOUSING - POM, black .
CONTACT/TERMINALS - Copper alloy, Silver or Gold plated .
RoHS - 2002/95/EC

RATING :

R : 0.4 Volt-Amps(VA) max. @20V max.(AC or DC)
 Q : 1Amp @250VAC
 3Amps @120 VAC or 28 VDC

| | | | | |
|--------------|--------------------------|------------|---|---|
| 焯倫股份有限公司 | PART NO. SLSW51-R02-1X03 | | TOLERANCES ARE X. ± .X ± 0.40 .XX ± 0.25 .XXX ± ANG ± 5° | DESCRIPTION: Sub - Miniature Rocker Switches |
| | UNIT / mm | SCALE 1:1 | | |
| | | | DRAWING BY | REVISIONS |
| | | PROJECTION | | DATE |