


General specifications

Circuit : ON-ON(2P2T)
 Rating : 6A 125 V AC
 3A 250 V AC
 Contact R.[max] : D.C. 5V 1A 100 mΩ
 Insulation R.[min]: D.C. 500 V 100 MΩ
 Withstand VOL. : A.C. 1,500 V 1 minute
 Operating force : 450± 150 g
 Life cycle[max] : 6,000 CYCLES

SCHEMATIC



材質表

NO	部品名稱	部品材質
1	動作桿 KNON	PA66
2	鐵殼 IRON SHEL	鐵鍍鎳 SPCC Ni-Plated
3	端子 TERMINAL	銅鍍銀 BRASS Ag-Plated
4	電木板 PC BOAR	電木板 PF
5	接觸片 CONTACT	磷青銅 PFC5191-H Ag

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY X.± 0.80
 CHECKED BY GENIUS .X± 0.50
 UNIT / mm SCALE 1:1 .XX± 0.30
 DATE .XXX±
 SIZE A4 PPROJECTION ANG ± 5°

照片框

ORDER INFORMATION

SLSW72-SPE087-2X03-LF
 SERIES | LEADFREE
 | 06 WAY
 | 8.7mm KNOB LENGTH
 | PANEL
 | SOLDER

DESCRIPTION: Slide Switch