



RECOMMENDED FOOTPRINT

| NO. | DESCRIPTION | MATERIALS | FINISHED |
|-----|-------------|------------|------------|
| 1 | BODY | BRASS | Gold |
| 2 | CONTACT | Be. Copper | Gold 30 μ" |
| 3 | INSULATOR | TEFLON | |

ELECTRICAL PERFORMANCE :

IMPEDANCE : 50 OHMS
 FREQUENCY : DC-12.4GHz
 WORKING VOLTAGE : 500 VRMS MAX.
 DIELECTRIC WITHSTANDING VOLTAGE : 1000 VRMS MAX.
 INSULATOR RESISTANCE : 5000 MEGOHMS MIN.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES
 煜倫股份有限公司

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ± 0.20
 .X ± 0.10
 .XX ± 0.05
 .XXX ±
 ANG ±

P PROJECTION



ORDER INFORMATION

SMA-JV-50-LF
 SERIES | T LEADFREE
 50 WAY
 180°SMT
 JACK

DESCRIPTION: SMA Female S/T for Surface Mount

www.morethanall.com